



MINI 46K-60
 MINI 46K-130

code 28540
 code 28550

G157a

50
l/min



IDENTIFICATION:
 - through PIN code
 or
 - through identification key



Protected switch



Manual starting key to supply in a emergency case



■ **Optional**
 Pedestal base

	Users	Memory Services
MINI 46K-60	60	200
MINI 46K-130	130	500

mm (approx.) 405
 400 460 kg (approx.) 24

*Maximum size and weight, without hose and nozzle

➤ **USE**

- The MINI supply kits are suitable for the diesel supply, measuring, and control of own consumption vehicles.
- Their installation is also suitable and/or advisable to the transport, private vehicle fleets, agriculture companies, ...

➤ **COMPOSED OF:**

CHASSIS

- Made of steel with interior and exterior treatment against corrosion. Weatherproof.

AG-46 Pump

- Self-suction, eccentric with self-adjusting blades
- Flow with free flow: 50 l/min
- Motor: 0,25 kW 230 VAC 50 Hz · IP-55 protection

Meter

- MGE-80A aluminium · Accuracy ±1 %

■ **GK-7 ELECTRONIC OWN CONSUMPTION CONTROLLER**

- The GK-7 electronic own consumption controller is suitable for the supply control, allowing its use only to authorized personnel.
- **User and/or vehicle identification through codes and/or identification key**
- **Supply with or without litre preset**

It controls:

- Supply date and hour
- User: 60 or 130 (according to the model)
- Vehicle
- Supplied litres
- Kilometers (or hours) and consumption
- Litre tank stock

The data are stored in memory and can be passed to a PC through communication by:

- Memory key (we charge the data in the key from the supply kit, and we discharge them in the PC) · only in the option of 60 users
- USB Cable
- GSM
- ETHERNET

The consult and configuration operations can be made from the PC, through the GK-7 SOFTWARE, or directly from the supply kit having the code or de Supervisor key that also could make the following:

- To enter or cancel users and/or vehicles
- To assign or change codes or identification keys (users and/or vehicles)
- To calibrate the kit
- To consult the done supplies
- To consult and regularize the tank stock
- To shape communication and other controller options

■ **Optional accessories:**



• Memory key code **251201001**

• GK-7 communication kit via memory key (software + converter + 1 memory key)
 code **257120000**

COMMUNICATION WITH KEY MAXIMUM 200 SERVICES AND 100 USERS



- GK-7 communication kit via USB cable (software + converter)
 code **257160000**



- GK-7 communication kit via ETHERNET (software + converter)
 code **257130000**



- GK-7 communication kit via MODEM/GSM (software + converter)
 code **257140000**

➤ **IT IS SUPPLIED WITH**

- 4 m delivery diesel hose Ø25 mm double layer with adapters in both ends
- PA-60 automatic nozzle

➤ **ACCESSORIES**

- F1" aluminium flange
- Pedestal Base (height of 1 m)
- FG-2 transparent microfilter of 2 litre capacity

