



**80**  
**l/min**



**IDENTIFICATION:**  
 - through PIN code  
 or  
 - through identification key



Protected switch




**Manual starting key** to supply in a emergency case



■ **Optional**  
 Pedestal base

	Users	Memory Services
<b>MINI 88K-60</b>	<b>60</b>	<b>200</b>
<b>MINI 88K-130</b>	<b>130</b>	<b>500</b>



\*Maximum size and weight, without hose and nozzle

➤ **USE**

- The MINI supply kits are suitable for the diesel supply, measuring and control of own consumption vehicles.
- Their installation is also suitable and/or advisable to the transport, private vehicle fleets, agriculture companies, ...

➤ **COMPOSED OF:**

**CHASSIS**

- Made of steel with interior and exterior treatment against corrosion. Weatherproof.

**AG-88 0,74kW Pump**

- Self-suction, eccentric with self-adjusting blades
- Flow with free outlet: 70-80 l/min
- Motor: 0,74 kW 230 VAC 50 Hz · IP-55 protection

**Meter**

- MGE-80A aluminium · Accuracy ±1 %

■ **GK-7 ELECTRONIC OWN CONSUMPTION CONTROLLER**

- The GK-7 electronic own consumption controller is suitable for the supply control, allowing its use only to authorized personnel.
- **User and/or vehicle identification** through **codes and/or identification key**
- **Supply with or without litre preset**

It controls:

- Supply date and hour
- User: 60 or 130 (according to the model)
- Vehicle
- Supplied litres
- Kilometers (or hours) and consumption
- Litre tank stock

The data are stored in memory and can be passed to a PC through communication by:

- Memory key (we charge the data in the key from the supply kit and we discharge them in the PC) · only in the option of 60 users
- Cable (RS232-485) or cable USB
- GSM
- ETHERNET

The consult and configuration operations can be made from the PC, through the GK-7 SOFTWARE, or directly from the supply kit having the code or de Supervisor key, that also could make the following:

- To enter or cancel users and/or vehicles
- To assign or change codes or identification keys (users and/or vehicles)
- To calibrate the kit
- To consult the done supplies
- To consult and regularize the tank stock
- To shape communication and other controller options

■ **Optional accessories:**



• Memory key code **251201001**

• GK-7 communication kit via memory key (software + converter + 1 memory key)  
 code **257120000**

**COMMUNICATION WITH KEY MAXIMUM 200 SERVICES AND 100 USERS**



- GK-7 communication kit via cable (software + converter)  
 code **257110000**
- GK-7 communication kit via cable USB (software + converter)  
 code **257160000**



- GK-7 communication kit via ETHERNET (software + converter)  
 code **257130000**



- GK-7 communication kit via MODEM/GSM (software + converter)  
 code **257140000**

> **IT IS SUPPLIED WITH**

- 4 m delivery diesel hose Ø25 mm double layer with adapters in both ends
- PA-80 automatic nozzle

> **ACCESSORIES**

- F1" aluminium flange
- Pedestal Base (height of 1 m)
- FG-2 transparent microfilter of 2 litre capacity

